

TTAME













Tam

Steel Stool

The TAM collection is based on the circle as the minimal unit of expression, an essential element that gives rise to organic and versatile configurations. Its modular design allows for an infinite number of compositions, from individual pieces to complex structures, fostering flexible connections between users. TAM is a customizable collection that adapts to every space and need, combining design with functionality.

DESIGNED BY NAHTRANG





DIMENSIONS

H45:

36cm x 36 cm x 46 cm x 46 cm
[width x depth x height x seat
height x seat height]

H45 with backrest:

36cm x 41 cm x 63 cm x 46 cm
[width x depth x height x seat
height x seat height]

H65:

40cm x 40 cm x 66 cm x 66 cm x
20 cm [width x depth x height x
seat height x footrest height]

H65 with backrest:

40cm x 43 cm x 83 cm x 66 cm x
20 cm [width x depth x height x
seat height x footrest height]

H75:

42cm x 42 cm x 76 cm x 76 cm x
30 cm [width x depth x height x
seat height x footrest height]

H75 with backrest:

42cm x 44 cm x 93 cm x 76 cm x
30 cm [width x depth x height x
seat height x footrest height]

WEIGHT

H45 [without/with backrest]: 3.75kg /
4.35kg

H65 [without/with backrest]: 5.15kg /
5.75kg

H75 [without/with backrest]: 5.65kg /
6.25 kg

PACKAGING

H45:

44 cm x 42 cm x 79 cm (1 piece per box)

55.3 cm x 41 cm x 97.5 cm (2 pieces per box)

H45 with backrest:

44 cm x 42 cm x 79 cm (1 piece per box)

55.3 cm x 41 cm x 97.5 cm (2 pieces per box)

H65:

44 cm x 42 cm x 79 cm (1 piece per box)

H65 with backrest:

44 cm x 42 cm x 90 cm (1 piece per box)

H75:

44 cm x 42 cm x 90 cm (1 piece per box)

H75 with backrest:

55.3 cm x 45 cm x 97.5 cm (1 piece per box)

CERTIFICATION

Product tested under the European standard EN
16139:2013, category of severe use L2.

PEFC certify wood.

ACCESORIES

Felt Glides

Backrest

ORIGIN

100% Made in Europe

DESIGN

Nahtrang



COMPONENTS

FRAME

Material

Cylindrical precision tube structure with a diameter of 25 mm (0.98") and a thickness of 2 mm (0.08") in recycled cold-rolled steel of E-220 quality (EN-10305 normative).

Tensile Strength > 403 N/mm² (58,438 psi);

Elastic limit >360 N/mm² (52,213 psi); Elongation > 29 %

Footrest in 18mm (0.72") diameter, 2mm (0.08") thick precision-rolled cylindrical tube in cold rolled steel, E220 quality (EN 10305 normative).

Tensile Strength > 310 N/mm² (33,962psi);

Elastic limit > 220 N/mm² (31,908 psi); Elongation >23 %

Finish

Epoxy Color

SEAT

Oak

Oak wood on birch plywood of 340mm diameter and 25 mm thickness, composed of reinforced lamellas with alternate arrangement of fibres to gain strength, glued, pressed and CNC machined with rounded edge.

Arpa Fenix + birch plywood

HPL high pressure laminate glued and pressed at high temperatures on a plywood core of 340 mm diameter and 25 mm thickness, consisting of reinforced sheets with alternating fibre arrangement for strength, glued, pressed and CNC-machined with rounded edges.

Upholstered

CNC machined 16 mm thick technical wood interior with 30 mm thick medium density flexible foam.

Upholstered seat-pad

Oak wood on birch plywood 340mm in diameter and 18 mm thick, composed of reinforced sheets with an alternating arrangement of fibres to gain strength, glued, pressed and CNC-machined with rounded edges. On it is included a piece of technical wood and flexible medium-density foam upholstered to offer greater comfort.

Finish

Stained oak, Fenix laminate, upholstery and seat-pad upholstery.



BACKREST

Easily assembled and disassembled accessory made from a 25 mm (0.98") diameter, 2 mm (0.08") thick precision bent cylindrical tube in recycled, cold-rolled steel of quality E-220 (norm EN-10305).

Tensile strength > 403 N/mm² (58,438 psi);

Elastic limit > 360 N/mm² (52,213 psi); Elongation > 29 %

METAL FINISHES

EPOXYS

Powder covering formulated with polyester resins, with good both mechanical and chemical properties, outdoor maximum resistance and noxious compounds free. Electrostatic application and oven cured at 200°C (392°F).

Technical characteristics:

Thickness (ISO 2360): between 60 and 90 µm.

Adherence (ISO 2409): Grade: 0 (maximum adherence)

WOOD FINISHES

STAINS

Pigmented enamel base coat and final coating in transparent silky touch dye. Reactive drying paints: excellent adherence between layers and better mechanical resistance.

Technical characteristics:

Complies with requirements outlined by UNE-EN 71-3; All compounds free of formaldehydes.

COM REQUIREMENTS

Seat with seat-pad: 50 cm*

Fully upholstered seat: 50 cm*

* For a width of 140cm you can get up to 3 pieces per 50cm.